

sales@awaretech.com

STAT FAX® 2200

Programmable Open System

ELISA Microplate - Digital Dry Bath



Stat Fax® 2200 Digital Dry Bath

Features

- Holds two 96-well microplates.
- Digitally controlled 8-speed mixer with orbital mixing from 575 to 1500 rpm.
- Temperature adjustable from ambient to 40°C with resolution of 0.1°C
- Digital timer controls mixing or can be operated independently, solely as a timer.
- Compact and easy to operate
- Outer tinted cover provides further insulation and protection from light.

Options & Accessories

Available with either 120V AC or 230V AC adapter.
37°C temperature calibration plate.

 **AWARENESS**
TECHNOLOGY, INC.

www.awaretech.com

STAT FAX® 2200

ELISA Microplate - Digital Dry Bath

Temperature range	Ambient to 40° C
Resolution	0.1° C
Uniformity with cover	Better than +/- .4° C
Mechanism	Enclosed, warm aluminum bed with air circulation
MIXER	
Speeds	8 gradual steps from 575 to 1500 RPM,
Options	Continuous or pulse
Mechanism	Rotating counter weight
Timer	
Modes	Set time, view time remaining, audible signal (stop mixing but maintains temperature control after time out)
Resolution	1 second
Range	1 second to 99 minutes, 59 seconds
Electronic	
Display	Four 7 segment red LEDs.
Keyboard	16-key, domed membrane switch, enunciating
Power requirements	12 V AC, 2 amps. Adapters available for 120 V or 230 V power with US or Euro plugs
Certifications	NRTL Listed, CE Mark
Vessel	Holds 2 standard microwell plates or strip trays
Dimensions and weight	Approx. 11" x 12.5" x 5.75", 7.2 lbs Approx. 43 cm x 37 cm x 18 cm, 3.3 kg



Awareness Technology, Inc. USA & International
tel: +1 772 283 6540 fax: +1 772 283 8020

Awareness Technology, Inc. Europe
tel: +43 (0) 2236 892465 fax: +43 (0) 2236 892464

Awareness Technology, Inc. Asia & Africa
tel: +971 (06) 557 80 58 fax: +971 (06) 557 80 59

ISO 13485:2016

